



LEINOS HARD OIL 240

Safe for the nursery. Hard for the whole house.

*A natural penetrating oil, certified to the toy-safety standard —
tough enough for every floor, door and stair.*





THE TRADE-OFF

Tough usually means
a plastic shell.

It chips where children play.

It seals the wood under film.

And you still wonder what is in it.

You should not have to choose.



PERMISSION

Certified safe for the room you worry about most.

*Tested to the same toy-safety standard as children's toys.
Open-pored and breathable — the wood stays wood.*



WHAT IT IS

One natural oil. Every surface underhand.

Linseed, wood and castor oils. Open-pored, deep-penetrating.

Certified to DIN EN 71-3 and DIN 53160 — the toy-safety standards.

Water-repellent. Vapour-permeable. Built for heavy wear.

9 shades + NCS custom tinting. About 130 to 180 sq ft per litre. Min 2 coats.

1



2



3



4



THE FULL SYSTEM

Four steps. Natural throughout.

- 1 • Hard Oil 240 — two thin penetrating coats (self-priming on absorbent wood)
- 2 • Hard Oil Special 245 — optional resin-rich, wax finish for extra-heavy wear
- 3 • Vegetable Soap 930 — regular cleaning, damp not wet
- 4 • Wood Care Balm 311 — food-safe refresh for furniture and worktops

Article numbers order-ready. Shades matched at the LEINOS Delhi lab.



TRUST

Founded by a pharmacist.
Made in Germany since 1985.

*Reincke Naturfarben, Horneburg.
Every ingredient declared on the can.*



HONEST COMPARISON

Penetrating oil. vs Film finish.

	LEINOS HARD OIL 240	FILM FINISH (PU / LACQUER)
MECHANISM	hardens inside the wood	plastic film on the surface
REPAIR	re-oil worn spots, no re-sand	chip or peel, then re-sand
BREATHABILITY	open-pore, vapour-permeable	sealed film
CHILD-SAFETY	certified DIN EN 71-3	often uncertified
FEEL	natural wood touch	plastic sheen





THE RITUAL

Brush on. Wipe off. Live on it.

Two thin coats • wet-on-wet possible • recoat in 16 to 24 hours.
Walkable in about a day. Cleaned with LEINOS Vegetable Soap 930.



APPLICATION TECHNICAL

For the specifier.

Substrate	• absorbent interior wood, cork, unglazed clay / terracotta tiles
Tools	• brush • roller • cloth • spray • dip
Coats	• two minimum • wet-on-wet possible • remove excess after final coat
Drying	• dust-dry 10 to 12 h • walkable and recoat 16 to 24 h • ventilate
Coverage	• about 130 to 180 sq ft per litre per coat • VOC 440 g/l (EU class F)
Standards	• DIN EN 71-3 toy safety • DIN 53160 saliva and sweat resistance



PROFESSIONAL TRUST

Specified for Indian interiors.

*From children's furniture and heritage doors
to high-traffic stairs and terracotta floors —
one natural oil the architect can specify with confidence.*

Reference projects available on request.



NEXT STEP

Reply to this message.

*A LEINOS specialist is one reply away.
We will calculate exact coverage for your surfaces
and match any shade at our Delhi lab.*

WhatsApp · +91 9997897474
sales@leinos.in · www.leinos.in

LEINOS Organic Paints Pvt. Ltd.

Khasra No. 646/1, Road No. Zero, Bakshi Farm Road,
Ghitorni, 110030 New Delhi

