




LEINOS HARDWAX OIL 290

Made for floors that don't wear shoes.

*Silky-matte hardwax oil.
DIN-certified for commercial floors.*





THE WRONG DEFENSE

Most finishes treat your floor
like it's about to be attacked.

*PU varnish armours.
Wax polish surrenders.
Both fight the foot — and lose.*

There is a third way.



PERMISSION

290 is the only finish
that gets better the more
you walk on it.

*Three components — oil, wax, resin —
that work with the foot, not against it.*



WHAT IT IS

Three components. One certified test.

Natural oils + Natural waxes + Resin binder.

DIN 68861-1 Service Group 1 A — abrasion certified.

Open-pore vapour-permeable. Wear-resistant. Water-repellent.
11 shades + NCS custom tinting. ~270 sq ft per litre. Min 2 coats.

1



2



3



4




THE FULL SYSTEM

Four steps. Natural-mineral throughout.

- 1 • Hard Oil 240 (primer for highly absorbent substrates like cork — optional on standard hardwood)
- 2 • Hardwax Oil 290 (base + colourless topcoat)
- 3 • Vegetable Soap 930 (regular cleaning • 10-30 ml per 10 L water, damp not wet)
- 4 • Care Oil 285 (initial care 4 weeks post-install for heavy-traffic • refresh on wear)

Full system from approximately ₹40 per square foot installed.



Wachsen

TRUST

Founded by a pharmacist.
Made in Germany since 1985.

*Reincke Naturfarben, Horneburg.
The same hardwax oil specified for
European boutique hospitality.*



HONEST COMPARISON

Hardwax oil. vs Polyurethane.

	LEINOS HARDWAX OIL 290	POLYURETHANE VARNISH
MECHANISM	oil + wax + resin penetrates	plastic film on top
REPAIR	spot-repair, no re-sand	full re-sand at year 5
VAPOUR	open-pore, vapour-permeable	sealed plastic film
PATINA	deepens with footfall	yellowes, peels, dulls
TEST	DIN 68861-1 SG 1A	varies, often unrated



YEAR ONE

COMPOUNDS IN BEAUTY

A specification, not a finish.

About ₹37 per square foot for two coats.
10L Colourless covers 2691 sq ft.
Spot-repairable forever. Never re-sand.
The only finish whose patina is the proof.

YEAR FIVE






THE RITUAL

Apply thinly.
Walk in three days.

Two coats · 16–24 h between · Full cure 7–14 days · Live for decades.
Cleaned with LEINOS Vegetable Soap 930.





APPLICATION TECHNICAL

For the specifier.

Substrate	dry, clean, dust-free, absorbent wood (max 14% moisture)
Tools	short-pile sealing roller • brush • cloth • white pad
Coats	two minimum • 16–24 hours between • third for high-wear
Conditions	ambient + surface > 15 °C • 50–55% RH ideal
Cure	walk-on 3 days • light traffic 7 days • full cure 7–14 days



PROFESSIONAL TRUST

Specified for Indian floors.

*From boutique hospitality to restored havelis
to modern duplex apartments —
hardwax oil is the architect's specification for
hardwood floors.*

*Reference projects available on request.



NEXT STEP

Reply to this message.

*A LEINOS specialist is one reply away.
We will calculate exact coverage for your floor
and walk you through the hardwax-oil system.*



WhatsApp · +91 9997897474
sales@leinos.in · www.leinos.in
LEINOS Organic Paints Pvt. Ltd.

Khasra No. 646/1, Road No. Zero, Bakshi Farm Road, Ghitorni, 110030 New Delhi