

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

Revision date: 04.01.2022

### Teak Oil outdoors

Product code: L-223

Page 1 of 8

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Teak Oil outdoors

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Vegetable resin paints

### 1.3. Details of the supplier of the safety data sheet

Company name:	LEINOS Naturfarben	
	Reincke Naturfarben GmbH	
Street:	Industriestraße 3	
Place:	D-21640 Horneburg	
Telephone:	+49 (0)4163-86 747-0	Telefax: +49 (0)4163-86 747-29
E-mail:	info@leinos.de	
E-mail (Contact person):	reincke.naturfarben@t-online.de	
Internet:	www.leinos.de	
Responsible Department:	+49 (0)4163-86 747-0 (8:00 - 17:00 h)	

**1.4. Emergency telephone number:** +49 (0)4163-86 747-0 (8:00 - 17:00 h)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

##### Hazard statements

H412 Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P273 Avoid release to the environment.  
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

##### Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH208 Contains Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction.

### 2.3. Other hazards

Spontaneous ignition possible through autoxidation of cloths soaked in the product.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Teak Oil outdoors**

Revision date: 04.01.2022

Product code: L-223

Page 2 of 8

**Relevant ingredients**

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
	Hydrocarbons, C10-C13, < 2 % aromatic compounds	40-50 %
	918-481-9	
	Asp. Tox. 1; H304 EUH066	
55406-53-6	Iodo-2-propynyl-butylcarbamate	0,6 %
	259-627-5	
	Acute Tox. 3, Acute Tox. 4, Eye Dam. 1, Skin Sens. 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H331 H302 H318 H317 H372 H400 H410	
27253-32-3	Manganese Neodecanoate	0,1 - < 0,5 %
	248-374-6	
	STOT RE 2; H373	
39049-04-2	Zirconium neodecanic acid salt	0,1 - < 0,5 %
	254-259-1	
	01-2120770770-52	
27253-29-8	Zinc Neodecanoate	0,1 - < 0,5 %
	01-2119978981-18	
	Aquatic Chronic 3; H412	

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
55406-53-6	259-627-5	Iodo-2-propynyl-butylcarbamate	0,6 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: ATE = 500 mg/kg	

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

When in doubt or if symptoms are observed, get medical advice.

Never give anything by mouth to an unconscious person or a person with cramps.

If unconscious but breathing normally, place in recovery position and seek medical advice.

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

**After contact with skin**

Immediately remove any contaminated clothing, shoes or stockings.

After contact with skin, wash immediately with plenty of water and soap.

Do not wash with: Solvents/Thinner

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids

apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious).

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Teak Oil outdoors

Revision date: 04.01.2022

Product code: L-223

Page 3 of 8

Call a physician immediately.  
Put victim at rest, cover with a blanket and keep warm.  
Do NOT induce vomiting.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Extinguishing powder, Water mist

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Hazardous decomposition products: carbon black. Danger of serious damage to health by prolonged exposure.

Use appropriate respiratory protection.

### 5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking. Ventilate affected area.

Avoid breathing dust/fume/gas/mist/vapours/spray.

See protective measures under point 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

#### Other information

Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal. Disposal: see section 13

Clean with detergents. Avoid solvent cleaners.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. Only use the material in places where open light, fire and other flammable sources can be kept away.

Use explosion-proof electrical equipment. Filling and transfer: Take precautionary measures against static discharges. Provide earthing of containers, equipment, pumps and ventilation facilities. Wear anti-static footwear and clothing Use only antistatically equipped (spark-free) tools.

Avoid contact with skin, eyes and clothes. Avoid: Inhalation of vapours or spray/mists, Inhalation of dust/particles. When using do not eat, drink or smoke.

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Teak Oil outdoors

Revision date: 04.01.2022

Product code: L-223

Page 4 of 8

#### Advice on protection against fire and explosion

Solvent - Vapours are heavier than air, spread along floors and form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Store in accordance with: Betriebssicherheitsverordnung (BetrSichV).

##### Hints on joint storage

Do not store together with: Oxidising agent, Strong acid, Strong alkali

##### Further information on storage conditions

Follow the instructions for use on the label.

storage temperature of °C 5 up to °C 30.

Keep container tightly closed in a cool, well-ventilated place. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in a place accessible by authorized persons only. Always close containers tightly after the removal of product.

#### 7.3. Specific end use(s)

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.2. Exposure controls

##### Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Wear eye/face protection.

##### Hand protection

Wear suitable gloves. Replace when worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. See information supplied by the manufacturer.

Suitable material: Nitrilkautschuk

Breakthrough time:: >= 8 hmin.

Use protective skin cream before handling the product.

##### Skin protection

Wear anti-static footwear and clothing (Natural fibres (e.g. cotton) / heat-resistant synthetic fibres)

##### Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values.

Use suitable breathing apparatus.

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	flüssig
Colour:	bräunlich
Odour:	mild, nach Ölen und Wachsen

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Teak Oil outdoors

Revision date: 04.01.2022

Product code: L-223

Page 5 of 8

#### Test method

Melting point/freezing point:	n.a.
Boiling point or initial boiling point and boiling range:	> 180 °C
Flammability:	n.a.
Lower explosion limits:	0,6 g/m <sup>3</sup>
Upper explosion limits:	7,0 g/m <sup>3</sup>
Flash point:	> 61 °C DIN 53213
Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s
Water solubility:	n.a.
Partition coefficient n-octanol/water:	n.a.
Density (at 20 °C):	0,87 g/cm <sup>3</sup> DIN 53217
Bulk density:	n.a.
Relative vapour density:	n.a.

#### 9.2. Other information

##### Information with regard to physical hazard classes

Sustaining combustion:	Not sustaining combustion	UN Test L.2
Self-ignition temperature		
Solid:		n.a.
Gas:		n.a.

##### Other safety characteristics

Evaporation rate:	n.a.	
Solvent content:	420 g/l	
Sublimation point:	n.a.	
Softening point:	n.a.	
Pour point:	n.a.	
Flow time: (at 40 °C)	> 60 s	3 DIN EN ISO 2431

## SECTION 10: Stability and reactivity

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Exothermic reaction with: Oxidising agent, Strong acid, Strong alkali

### 10.4. Conditions to avoid

In case of warming: Formation of: Hazardous decomposition products

### 10.6. Hazardous decomposition products

Nitrogen oxides (NO<sub>x</sub>), carbon black, Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) 500,0 mg/l; ATE (inhalation dust/mist) 83,33 mg/l

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Teak Oil outdoors

Revision date: 04.01.2022

Product code: L-223

Page 6 of 8

#### Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
55406-53-6	Iodo-2-propynyl-butylcarbamate				
	oral	ATE 500 mg/kg			
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			

#### Practical experience

Following inhalation:

Potential hazards: May cause respiratory irritation. Depression of central nervous system.

Symptoms: Headache, Dizziness, Dizziness, Unconsciousness

After eye contact:

Irritating to eyes. (reversible.)

Following ingestion:

Symptoms: Nausea, Vomiting, Gastrointestinal complaints

Following skin contact:

The product is skin resorptive. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

#### 11.2. Information on other hazards

##### Further information

There are no data available on the mixture itself.

Reference to other sections: 2, 3

### SECTION 12: Ecological information

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

##### Further information

There are no data available on the mixture itself.

Do not allow to enter into surface water or drains.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Disposal recommendations

Do not allow to enter into surface water or drains.

Dispose according to legislation.

##### List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

##### List of Wastes Code - used product

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Teak Oil outdoors

Revision date: 04.01.2022

Product code: L-223

Page 7 of 8

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

#### Contaminated packaging

Completely emptied packages can be recycled.  
Dispose according to legislation.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### Inland waterways transport (ADN)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### Marine transport (IMDG)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.  
**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.  
**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.  
**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Directive 2004/42/EC on VOC in paints and varnishes: ChemVOFarbV 420 g/l : Kategorie f

##### National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

##### Additional information

Observe in addition any national regulations!

### SECTION 16: Other information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Teak Oil outdoors**

Revision date: 04.01.2022

Product code: L-223

Page 8 of 8

**Abbreviations and acronyms**

Acute Tox: Acute toxicity  
Asp. Tox: Aspiration hazard  
Eye Dam: Eye damage  
Skin Sens: Skin sensitisation  
STOT RE: Specific target organ toxicity - repeated exposure  
Aquatic Acute: Acute aquatic hazard  
Aquatic Chronic: Chronic aquatic hazard

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H331 Toxic if inhaled.  
H372 Causes damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.  
EUH208 Contains Iodo-2-propynyl-butylcarbamate. May produce an allergic reaction.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*