



Impregnation Wood Primer 150

Impregnation wood primer for interior and exterior use. Designed as an open-pore primer for subsequent varnish or glaze coatings on wooden surfaces.

Drying Time

Approx. 16–24 hours at 20°C and 50–55% RH. Ensure good fresh air circulation during drying.

Coverage

Coverage: approx. 130–180 sq ft per litre per coat, depending on surface condition.

Technical Qualities

Deeply penetrating wood primer

Vapour-permeable

Strengthens wood

Film protection against fungal attack (blue stain)

Light absorbent wood may dry slightly darker

Safety Recommendations

Store away from children.

Avoid release to the environment.

Oil-soaked application materials pose a spontaneous combustion risk. Store used cloths, sponges, and sanding dust immediately in a sealed metal container or in water before disposal.

When spraying, wear approved respiratory protection.

Contains Iodo-2-propynyl-butyl-carbamate. See SDS for hazard and precautionary statements.



Impregnation Wood Primer 150

Impregnation wood primer for interior and exterior use. Designed as an open-pore primer for subsequent varnish or glaze coatings on wooden surfaces.

Application Instructions

Stir well before use.

Apply undiluted and evenly.

Apply a generous coat; after ~20 minutes redistribute any glossy excess.

Allow to dry fully before overcoating.

Tools: Brush, Roller, Spray, Dipping.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in