



Teak Oil 223

Penetrating exterior wood oil for protection and maintenance of outdoor timber

For the first-time treatment and care of exterior woodwork. Teak Oil is a high quality product based on vegetable oils and resins for all types of exterior wood such as fences, pergola, play ground timber, wooden terraces and decks, teak furniture and garden furniture. Suitable especially for tropical woods such as bangkirai and teak.

Drying Time

Dry to touch after approx. 6–8 hours.
Recoat after approx. 16–24 hours at 20 °C and average humidity.

Coverage

Coverage: approx. 150–215 sq ft per litre per coat, depending on surface condition.

Pack Size	Coverage
0,25l	4 m ²
0,75l	12,5 m ²
2,5l	41,5 m ²

Tool Cleaning

Immediately after use, clean tools with white spirit or a similar solvent.

Storage

Store in a dry and cool place, protect from freezing. Shelf life in closed packaging is at least 2 years.

Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 11.

Technical Qualities

Penetrating exterior wood oil
Impregnating oil for deep fibre protection
Vapour-permeable, open-pore finish
Water-resistant protection against moisture
Recoat for easy maintenance

Composition

Linseed oil, wood oil, castor oil, natural resin esters, isoparaffins, mineral pigments (except colorless), drying agents.

The maximum content of Volatile Organic Compounds (VOC) in this product is 420 g/l. It complies with the European VOC standard, which allows a maximum of 700 g/l (Category "f", EU Directive 2004/42/EC).

Safety Recommendations

Store away from children.
Avoid release to the environment.
Risk of spontaneous combustion of oil-soaked materials. Store used cloths in a sealed metal container filled with water or dispose of them safely.
Wear respiratory protection when spraying.

Technical Standards

DIN 53160

Teak Oil 223

Penetrating exterior wood oil for protection and maintenance of outdoor timber



Application Instructions

Penetrates deeply into the wood fibres without forming a surface film

Maintains the natural elasticity of wood and helps prevent drying and cracking

Designed for maintenance and renewal of exterior wood surfaces

Tools: Brush, Roller, Spray.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in