



Terrace Wood Oil 236

Penetrating oil-resin finish for exterior wood, designed for terraces, decking, and outdoor timber.

Drying Time

Dry after approx. 6–8 hours; recoatable after approx. 16–24 hours at 20 °C and average humidity.

Coverage

Coverage: approx. 140–250 sq ft per litre per coat, depending on surface condition.

Technical Qualities

Oil-resin finish for exterior wood
Deep penetration into wood fibres
Open-pore, vapor-permeable finish
Water-resistant protection against moisture
Recoatable; no sanding required for maintenance coats
Saliva and sweat resistant (DIN 53160)

Safety Recommendations

Store away from children.
Avoid release to the environment.
Risk of spontaneous combustion of oil-soaked materials. Store used cloths in an airtight metal container or in water before disposal.
Wear respiratory protection when spraying.



Terrace Wood Oil 236

Penetrating oil-resin finish for exterior wood, designed for terraces, decking, and outdoor timber.

Application Instructions

Ready to use; stir well before application.

Apply thinly and evenly; avoid puddles and excess material.

Apply only at temperatures above 10 °C; ensure adequate ventilation during drying.

Tools: Brush.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in