

## Hard Oil 240

Penetrating oil finish for absorbent interior surfaces

For the open-pored impregnation of all absorbent interior surfaces. For the open-pored impregnation of all absorbent interior surfaces, like wood, cork, non-glazed clay tiles, especially for surfaces exposed to wear and tear. The wear resistance of the surface can be enhanced by a finish with Hard Oil special 245.

### Color

Colorless, Pine, Walnut, Chestnut, Double White, Amber, White, Grey, Black.

### Drying Time

Dust-dry: approximately 10–12 hours.  
Walkable and recoatable: approximately 16–24 hours. Ensure sufficient air circulation during drying.

### Coverage

Coverage: approx. 130–180 sq ft per litre per coat, depending on surface condition.

| Pack Size | Coverage           |
|-----------|--------------------|
| 0,25l     | 4 m <sup>2</sup>   |
| 0,75l     | 12 m <sup>2</sup>  |
| 2,5l      | 40 m <sup>2</sup>  |
| 10l       | 160 m <sup>2</sup> |
| 30l       | 480 m <sup>2</sup> |

### Tool Cleaning

Immediately after use, clean tools with white spirit or a similar solvent.

### Storage

Store in a dry and cool place, protect from freezing. Shelf life in closed packaging is at least 2 years.

### Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 11.

### Technical Qualities

Water-repellent  
Water vapour permeable  
Deep-penetrating  
Ready to use  
Wet-on-wet application possible (second coat after short waiting time)

### Composition

Linseed oil, wood oil, castor oil, natural resin esters, isoparaffins, mineral pigments (except colorless), drying agents.

The maximum content of Volatile Organic Compounds (VOC) in this product is 440 g/l. It complies with the European VOC standard, which allows a maximum of 700 g/l (Category "F", EU Directive 2004/42/EC).

### Safety Recommendations

Oil-soaked rags and sanding dust are spontaneous combustion hazards.  
Store oil-soaked materials in a sealed metal container or under water until disposal.  
Store away from children.  
If swallowed: seek medical advice immediately; do not induce vomiting.  
Avoid release to the environment.  
Ensure adequate ventilation during drying.  
Wear approved respiratory protection (NIOSH P100 or CE equivalent) when spraying.  
Wear a particulate dust mask (P100 or CE FFP2 equivalent) when sanding.

### Technical Standards

DIN EN 71, part 3  
DIN 53160



## Hard Oil 240

Penetrating oil finish for absorbent interior surfaces

### Application Instructions

For absorbent interior substrates such as wood, cork, and unglazed terracotta.

Apply at least two coats.

A second coat can be applied wet-on-wet after a short waiting time.

Remove excess oil after the final coat.

**Tools:** Brush, Roller, Spray, Dip.

*This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.*

#### Manufacturer

Reincke Naturfarben GmbH  
Industriestraße 3  
21640 Horneburg, Germany  
Tel. +49 (0) 41 63 - 86 74 7-0  
[www.leinos.de](http://www.leinos.de)

#### Distributor in India

Leinos Organic Paints Private Limited  
GSTIN - 07AAFCL0615C1Z3  
646/1, Zero Number Rd, Anand Gram,  
Ghitorni, New Delhi 110030, India  
+919997897474 | [sales@leinos.in](mailto:sales@leinos.in)