



Stone and Concrete Oil 254

Colorless impregnation oil for absorbent tiles, terracotta, and chemically neutral concrete surfaces. Water-repellent and abrasion-resistant.

For surface treatment of all types of concrete and stoneware, indoors. For impregnating and maintaining all absorbent tiles and concrete surfaces, such as terracotta etc.

Drying Time

Dry and recoatable after 4-6 hours.
Complete curing approximately 7-10 days at 18-22°C.

Coverage

Coverage: approx. 215-540 sq ft per litre per coat, depending on surface absorbency.

Pack Size	Coverage
0.75l	21.5 m ²
2.5l	71.5 m ²
2,5l	63 m ²

Tool Cleaning

Immediately after use, clean tools with white spirit or a similar solvent.

Storage

Store in a dry and cool place, protect from freezing. Shelf life in closed packaging is at least 2 years.

Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 11.

Technical Qualities

Colorless surface coating
Water-repellent protection
Abrasion-resistant
Does not significantly darken surface
Suitable for interior and exterior use

Composition

Wood oil, linseed oil, castor oil, sunflower oil, natural resin ester, isoparaffins, desiccants
EU limit 700 g/l, cat f

Safety Recommendations

Store away from children.
Oil-soaked materials pose spontaneous ignition risk.
Ensure adequate ventilation during drying.
Use respiratory protection when spraying.



Stone and Concrete Oil 254

Colorless impregnation oil for absorbent tiles, terracotta, and chemically neutral concrete surfaces. Water-repellent and abrasion-resistant.

Application Instructions

Stir thoroughly.

Apply with brush, cloth, roller, or sponge.

Allow 20-30 minutes penetration.

Remove excess oil.

Apply second thin coat the next day.

No oil layer must remain on surface.

Tools: Brush, Cloth, Roller, Sponge.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in