



Hard Oil Universal 259

Versatile universal primer and topcoat for all interior wood types. Enhances natural wood structure with silky matte, durable, water-repellent finish.

Open-pored impregnation and finish of all absorbent interior surfaces like wood, cork, stairs and unglazed clay and brick tiles, OSB boards and furniture surfaces. Suitable especially for areas exposed to wear and tear. Hard-wearing, satin finish, water repellent, open-pored. Accentuates the natural wood grain. DIN EN 71 Part 3 certified as suitable for toys. German Industrial Norm (DIN) 53160 certified for colour fastness when exposed to perspiration and saliva. Water resistant according to DIN 68861 Part 1. Surfaces will be free of yellowing to a large extent.

Color

Colorless, White, Antique Grey.

Drying Time

Dust-dry approx. 6-8 hours. Foot traffic safe after 16-24 hours.

Coverage

Coverage: approx. 180-270 sq ft per litre per coat, depending on surface condition.

Pack Size	Coverage
0,25l	4 m ²
0,75l	12 m ²
2,5l	40 m ²
10l	160 m ²
30l	480 m ²

Tool Cleaning

Immediately after use, clean tools with white spirit or a similar solvent.

Storage

Store in a dry and cool place, protect from freezing. Shelf life in closed packaging is at least 2 years.

Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 11.

Technical Qualities

Universal primer and topcoat
Silky matte finish
Water-repellent
Largely yellowing-resistant
No intermediate sanding required

Composition

Linseed oil, wood oil-castor oil standoil, wood oil-standoil, natural resin esters, isoparaffins, drying agents
EU limit 700 g/l, cat f

Safety Recommendations

Harmful to aquatic organisms with long-term effects.
Oil-soaked materials pose spontaneous ignition risk.
Wear respiratory protection when spraying.

Technical Standards

DIN EN 71 Part 3
DIN 68861 Part 1



Hard Oil Universal 259

Versatile universal primer and topcoat for all interior wood types.
Enhances natural wood structure with silky matte, durable, water-repellent finish.

Application Instructions

Sand wood with 150-180 grit in grain direction.

Apply 3 uniform thin coats using sealing roller with 6-8 hour intervals.

No intermediate sanding required.

Tools: Brush, Roller, Spray, Sealing roller.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in