



Premium Wood Varnish 260

Exterior wood stain with weather-resistant, water-repellent, open-pore protection.

Drying Time

Approx. 16–24 hours under normal climate conditions. Ensure adequate ventilation during drying.

Coverage

Coverage: approx. 130–180 sq ft per litre per coat, depending on surface condition.

Tool Cleaning

Clean tools immediately after use with LEINOS Thinner 200.

Storage

Shelf life: at least 2 years in original sealed container. Store cool, dry, and tightly closed.

Technical Qualities

Water-repellent

Water vapour permeable (open-pore)

Weather-resistant

Includes fungicide protection against sapstain

Saliva and sweat resistant (DIN 53160)

Low chemical migration (tested per DIN EN 71-3 methodology)

Composition

Wood oil, Castor oil, Stand oil / natural resin esters, Isoparaffins, Micro wax, Mineral pigments, Zinc oxide, Preservative: Iodo-2-propynyl-butyl carbamate.

The maximum content of Volatile Organic Compounds (VOC) in this product is 480 g/l. It complies with the European VOC standard, which allows a maximum of 700 g/l (Category "f", EU Directive 2004/42/EC).

Safety Recommendations

Not suitable for children\

,
,
,
,
,
,
,



Premium Wood Varnish 260

Exterior wood stain with weather-resistant, water-repellent, open-pore protection.

Application Instructions

Conditions: Substrate must be dry, sound, clean, grease-free, dust-free, and absorbent. Ambient and surface temperature above 15 °C.

For absorbent exterior wooden substrates.

Apply evenly in the direction of the wood grain.

Apply at least two coats.

Ensure sufficient ventilation during drying.

Coats & recoating: At least two coats required. Recoat after drying of the previous coat.

Tools: Brush, Roller, Spray.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in