



Wood Varnish, Water-Based 266

Water-based exterior wood stain with weather-resistant, water-repellent, open-pore protection.

For all types of interior and exterior wooden surfaces. Water-based wood stain for all types of interior and exterior wood surfaces. Particularly suitable for softwoods but also for hardwoods and hardwoods for decorative coloring and protection against soiling and weathering. Not suitable for the final treatment of floors, stairs and other surfaces subject to particularly heavy wear.

Drying Time

Dry to touch: approx. 2–4 hours.
Recoat after approx. 6–8 hours.
Fully cured after approx. 24 hours.
Drying time depends on temperature, humidity, and ventilation.

Coverage

Coverage: approx. 90–135 sq ft per litre per coat, depending on surface condition.

Pack Size	Coverage
0,25l	3.5 m ²
0,75l	10 m ²
2,5l	34 m ²

Tool Cleaning

Clean tools immediately after use with water.

Storage

Shelf life: at least 12 months in original sealed container. Store frost-free, cool, and tightly closed.

Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 12.

Technical Qualities

Water-based
Water-repellent
Water vapour permeable (open-pore)
Weather-resistant
Saliva and sweat resistant (DIN 53160)
Low chemical migration (tested per DIN EN 71-3 methodology)

Composition

Water, Acrylic dispersion, Mineral pigments, Additives.
The maximum content of Volatile Organic Compounds (VOC) in this product is 30 g/l. It complies with the European VOC standard, which allows a maximum of 130 g/l (Category "a", EU Directive 2004/42/EC).

Safety Recommendations

Not suitable for children\

,
,
,
,
,



Wood Varnish, Water-Based 266

Water-based exterior wood stain with weather-resistant, water-repellent, open-pore protection.

Application Instructions

Conditions: Substrate must be dry, sound, clean, grease-free, dust-free, and absorbent. Ambient and surface temperature above 15 °C.

For absorbent exterior wood substrates.

Apply evenly in the direction of the wood grain.

Apply at least two coats.

Protect fresh coating from rain and moisture until dry.

Ensure sufficient ventilation during drying.

Coats & recoating: At least two coats required. Recoat after drying of the previous coat.

Tools: Brush, Roller, Spray.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in