



## Countertop Oil 280

Oil for interior wooden worktops and surfaces. Tested for migration according to EN 71-3.

### Drying Time

Dry to touch: approx. 6–12 hours.  
Recoat after approx. 12 hours.  
Ready for food contact once fully cured (approx. 7 days). Drying time depends on temperature, ventilation, and wood absorbency.

### Coverage

Coverage: approx. 190–320 sq ft per litre per coat, depending on surface condition.

### Tool Cleaning

Clean tools immediately after use with LEINOS Brush Cleaner or white spirit.

### Storage

Shelf life: at least 5 years in original sealed container. Store cool, dry, and tightly closed.

### Technical Qualities

Tested for migration according to EN 71-3  
Tested for migration according to EN 71-3  
Penetrating oil  
Open-pore, vapour-permeable surface finish  
Natural oil-based formulation

### Composition

Natural oils, Natural resins, Aliphatic hydrocarbons, Additives.  
The maximum content of Volatile Organic Compounds (VOC) in this product is 360 g/l. It complies with the European VOC standard, which allows a maximum of 700 g/l (Category "f", EU Directive 2004/42/EC).

### Safety Recommendations

Oil-soaked rags and application residues may spontaneously combust.  
Store oil-soaked materials in a sealed metal container or under water until disposal.  
Avoid contact with eyes, skin, and clothing.  
Avoid release to the environment.  
Ensure adequate ventilation during drying.



## Countertop Oil 280

Oil for interior wooden worktops and surfaces. Tested for migration according to EN 71-3.

### Application Instructions

**Conditions:** Substrate must be dry, clean, grease-free, dust-free, and absorbent. Ambient and surface temperature above 15 °C.

For absorbent interior wooden substrates.

Apply evenly with cloth, brush, or pad.

Allow oil to penetrate and remove excess.

Apply at least two coats.

Ensure sufficient ventilation during drying.

**Coats & recoating:** At least two coats recommended. Additional coats may be applied depending on absorbency.

**Tools:** Cloth, Brush, Pad.

*This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.*

#### Manufacturer

Reincke Naturfarben GmbH  
Industriestraße 3  
21640 Horneburg, Germany  
Tel. +49 (0) 41 63 - 86 74 7-0  
[www.leinos.de](http://www.leinos.de)

#### Distributor in India

Leinos Organic Paints Private Limited  
GSTIN - 07AAFCL0615C1Z3  
646/1, Zero Number Rd, Anand Gram,  
Ghitorni, New Delhi 110030, India  
+919997897474 | [sales@leinos.in](mailto:sales@leinos.in)