



Interior Hardwax Oil 290

Hardwax oil for durable protection and finishing of interior wooden surfaces.

Drying Time

Dry to touch: approx. 6–12 hours.
Recoat after approx. 12 hours. Fully cured after approx. 7–10 days. Drying time depends on temperature, ventilation, and wood absorbency.

Coverage

Coverage: approx. 190–320 sq ft per litre per coat, depending on surface condition.

Tool Cleaning

Clean tools immediately after use with LEINOS Brush Cleaner or white spirit.

Storage

Shelf life: at least 5 years in original sealed container. Store cool, dry, and tightly closed.

Technical Qualities

Combination of natural oils and waxes
Wear-resistant
Water-repellent
Open-pore, vapour-permeable
Dirt-resistant
Enhances wood grain and colour

Composition

Natural oils, Natural waxes, Aliphatic hydrocarbons, Additives.
The maximum content of Volatile Organic Compounds (VOC) in this product is 440 g/l. It complies with the European VOC standard, which allows a maximum of 500 g/l (Category "i", EU Directive 2004/42/EC).

Safety Recommendations

Oil-soaked rags and application residues may spontaneously combust.
Store oil-soaked materials in a sealed metal container or under water until disposal.
Avoid contact with eyes, skin, and clothing.
Avoid release to the environment.
Ensure adequate ventilation during drying.



Interior Hardwax Oil 290

Hardwax oil for durable protection and finishing of interior wooden surfaces.

Application Instructions

Conditions: Substrate must be dry, clean, grease-free, dust-free, and absorbent. Ambient and surface temperature above 15 °C.

For absorbent interior wooden substrates.

Apply thinly and evenly.

Allow oil to penetrate and remove excess.

Apply at least two coats.

Ensure sufficient ventilation during drying.

Coats & recoating: At least two coats recommended. Additional coats may be applied depending on absorbency and wear requirements.

Tools: Brush, Roller, Cloth, Pad.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in