



Wood Filler 337

High-quality wood filler in powder form for repairs and knots up to 15 mm deep. Compatible with all surface finishes, suitable for interior and exterior use.

Color

420 White, 421 Ash, 422 Oak, 423 Natural Oak, 424 Smoked Oak, 425 Oak Knot, 426 Cherry, 427 Beech, 428 Black.

Drying Time

Approximately 45 minutes before sanding.

Coverage

Coverage varies by application (powder product).

Tool Cleaning

Immediately after use, clean tools with white spirit or a similar solvent.

Storage

Store in a dry and cool place. Shelf life in closed packaging is at least 2 years.

Disposal

Dispose of according to official regulations.

Technical Qualities

Powder-form wood filler
Repairs up to 15 mm deep
Compatible with all finishes
Available in 9 colours
Water-based system

Composition

Calcium carbonate, calcium sulfate, mineral pigments

Safety Recommendations

Contains 1,2-benzisothiazol-3(2H)-one — may cause allergic reactions.
Do not inhale dust.
Keep away from children.



Wood Filler 337

High-quality wood filler in powder form for repairs and knots up to 15 mm deep. Compatible with all surface finishes, suitable for interior and exterior use.

Application Instructions

Mix powder with cold water at 3:1 ratio.

Apply within 20 minutes.

Sanding possible after approximately 45 minutes.

Tools: Spatula, Mixing container.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in