



## Wax Varnish 600

Wax-based wood varnish for decorative and protective treatment of exterior wooden surfaces.

Aqueous, colourless wax emulsion for the individual tinting with LEINOS Pigment Concentrate 668. For the coloured design of wooden ceiling-and wall covers and also for wooden furniture parts used in interior areas.

### Drying Time

Dry to touch: approx. 6–12 hours.  
Recoat after approx. 12–24 hours.  
Fully cured after several days. Drying time depends on temperature, humidity, ventilation, and wood absorbency.

### Coverage

Coverage: approx. 160–240 sq ft per litre per coat, depending on surface condition and wood absorbency.

Pack Size	Coverage
0,75l	9,5 m <sup>2</sup>
2,5l	31 m <sup>2</sup>
10l	125 m <sup>2</sup>

### Tool Cleaning

Clean tools immediately after use with water and mild soap.

### Storage

Shelf life: at least 2 years in original sealed container. Protect from frost. Store cool, dry, and tightly closed.

### Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 11.

### Technical Qualities

Wax-based protective finish  
Water-repellent  
Vapour-permeable  
Open-pore finish  
Weather-resistant  
Enhances wood grain and colour

### Composition

Natural waxes, Natural oils, Water, Additives.

The maximum content of Volatile Organic Compounds (VOC) in this product is 1 g/l. It complies with the European VOC standard, which allows a maximum of 30 g/l (Category "a", EU Directive 2004/42/EC).

### Safety Recommendations

Store away from children.  
Avoid contact with eyes and skin.  
Avoid release to the environment.  
Ensure adequate ventilation during application and drying.



## Wax Varnish 600

Wax-based wood varnish for decorative and protective treatment of exterior wooden surfaces.

### Application Instructions

**Conditions:** Substrate must be dry, clean, grease-free, dust-free, and absorbent. Ambient and surface temperature above 10 °C. Wood moisture content must be within normal range for exterior application.

For absorbent exterior wooden substrates.

Apply thinly and evenly in the direction of the wood grain.

Apply at least two coats.

Protect fresh coating from rain and moisture until dry.

Ensure sufficient ventilation during drying.

**Coats & recoating:** At least two coats recommended. Additional coats may be applied depending on exposure and wood absorbency.

**Tools:** Brush, Roller, Cloth.

*This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.*

#### Manufacturer

Reincke Naturfarben GmbH  
Industriestraße 3  
21640 Horneburg, Germany  
Tel. +49 (0) 41 63 - 86 74 7-0  
www.leinos.de

#### Distributor in India

Leinos Organic Paints Private Limited  
GSTIN - 07AAFCL0615C1Z3  
646/1, Zero Number Rd, Anand Gram,  
Ghitorni, New Delhi 110030, India  
+919997897474 | sales@leinos.in