



Furniture Chalk Paint 637

Decorative chalk paint for furniture and interior decorative surfaces.

Covering chalk paint for renovation indoors Open pored chalk paint according to DIN EN 13300 with very good covering power, easy to apply and versatile. For easily stressed surfaces indoors, e. g. furniture, wall paneling etc.

Color

630 Mint, 631 Ice Blue, 632 Savanna, 634 Vanilla, 635 Cream, 636 Tuscan Red, 637 Pacific Blue, 638 Stone Grey, 639 Dark Grey, 640 White.

Drying Time

Touch dry after approx. 1–2 hours.
Recoat after approx. 4–6 hours.
Fully cured after several days. Drying time depends on temperature, ventilation, and surface absorbency.

Coverage

Coverage: approx. 160–215 sq ft per litre per coat, depending on surface condition.

Tool Cleaning

Clean tools immediately after use with water and mild detergent.

Storage

Shelf life: at least 5 years in original sealed container. Store cool, dry, and tightly closed. Protect from frost.

Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 12.

Technical Qualities

Decorative chalk paint
Matt finish
Vapour-permeable
Open-pore finish
Low-odour
Suitable for vintage and shabby-chic decorative effects

Composition

Water, Natural resins, Mineral pigments, Additives.
The maximum content of Volatile Organic Compounds (VOC) in this product is 1 g/l. It complies with the European VOC standard, which allows a maximum of 30 g/l (Category "a", EU Directive 2004/42/EC).

Safety Recommendations

Ensure adequate ventilation during application and drying.
Avoid contact with eyes and skin.
Store away from children.
Avoid release to the environment.

Technical Standards

DIN EN 13300



Furniture Chalk Paint 637

Decorative chalk paint for furniture and interior decorative surfaces.

Application Instructions

Conditions: Substrate must be dry, clean, grease-free, dust-free, and stable. Previously painted surfaces must be sound and properly prepared. Ambient and surface temperature above 15 °C.

Suitable for furniture and interior decorative surfaces.

Suitable for wood and properly prepared interior surfaces.

Apply evenly.

Apply at least two coats.

Ensure adequate ventilation during drying.

Coats & recoating: At least two coats recommended. Additional coats may be applied depending on surface condition and desired decorative effect.

Tools: Brush, Roller.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in