



Interior White Paint 650

Interior white emulsion paint with low-odour, solvent-free, vapour-permeable finish for walls and ceilings.

Low odour, VOC-free, breathable. For white or coloured opaque coatings with good water vapor permeability on mineral bases or on wallpaper with firm and good adhesion.

Drying Time

Dry to touch: approx. 6–12 hours.
Recoat after approx. 16–24 hours.
Drying time depends on temperature, humidity, ventilation, and substrate absorbency.

Coverage

Approx. 150 ml/m² per coat. Coverage depends on substrate absorbency and surface condition.

Pack Size	Coverage
10l	66 m ²

Tool Cleaning

Clean tools immediately after use with water.

Storage

Store cool, dry, and frost-free. Keep container tightly closed. Shelf life: at least 12 months in original unopened container.

Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 12.

Technical Qualities

Water-based natural resin emulsion
Solvent-free
Low-odour
Vapour-permeable (Class 1, DIN EN ISO 7783-2)
Matt finish
High opacity
Washable (Class 3, DIN EN 13300)

Composition

Water, Natural resin binders, Mineral fillers, Natural additives, Preservatives (contains isothiazolinones).

The maximum content of Volatile Organic Compounds (VOC) in this product is 1 g/l. It complies with the European VOC standard, which allows a maximum of 30 g/l (Category "a", EU Directive 2004/42/EC).

Safety Recommendations

Store away from children.
Avoid contact with eyes and skin.
Contains isothiazolinones. See SDS for hazard and precautionary statements.
Ensure adequate ventilation during application and drying.
Avoid release to the environment.
Safety Data Sheet available on request.

Technical Standards

DIN EN 13300



Interior White Paint 650

Interior white emulsion paint with low-odour, solvent-free, vapour-permeable finish for walls and ceilings.

Application Instructions

Conditions: Substrate must be dry, clean, grease-free, dust-free, and absorbent. Strongly alkaline substrates must be neutralised before application. Ambient and surface temperature above 10 °C.

For absorbent, firmly adhering interior mineral substrates.

Apply evenly by brush or roller.

Apply undiluted or diluted with water as required.

Apply one to two coats depending on substrate and opacity requirements.

Ensure adequate ventilation during application and drying.

Coats & recoating: Typically one to two coats required. Recoat only after the previous coat has dried sufficiently.

Tools: Brush, Roller.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in