



Natural Resin Emulsion Paint 660

Natural resin emulsion paint for interior walls and ceilings with a matt, vapour-permeable finish.

Natural white, matt, VOC-free, breathable, for indoor use. Natural resin dispersion paint for indoor application, white or coloured. Suitable for all mineral surfaces and bonded wall paper.

Drying Time

Drying time: approx. 16–24 hours at 20 °C and 50 % relative humidity. Drying time may be extended under cooler or more humid conditions.

Coverage

Coverage: approx. 100–200 ml/m² per coat, depending on substrate absorbency.

Pack Size	Coverage
2,5l	16,5 m ²
10l	66 m ²

Tool Cleaning

Clean tools immediately after use with water.

Storage

Store cool, dry, and frost-free. Keep container tightly closed. Shelf life: at least 12 months in original sealed container.

Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 12.

Technical Qualities

Water-based natural resin emulsion
 Solvent-free, very low VOC content (< 1 g/L)
 Vapour-permeable (Class 1, DIN EN ISO 7783-2)
 Matt finish
 Good opacity (Covering power Class 2, DIN EN 13300)
 Wet scrub resistance Class 3 (DIN EN 13300)

Composition

Water, Natural resins, Mineral fillers and pigments, Additives.

The maximum content of Volatile Organic Compounds (VOC) in this product is 1 g/l. It complies with the European VOC standard, which allows a maximum of 30 g/l (Category "a", EU Directive 2004/42/EC).

Safety Recommendations

Store away from children.
 Avoid contact with eyes, skin, and clothing.
 Ensure adequate ventilation during application and drying.
 Dispose of residues according to local regulations.
 Safety Data Sheet available on request.

Technical Standards

DIN EN 13300



Natural Resin Emulsion Paint 660

Natural resin emulsion paint for interior walls and ceilings with a matt, vapour-permeable finish.

Application Instructions

Conditions: Substrate must be dry, clean, dust-free, and firmly adhering. Strongly alkaline substrates must be neutralised before application. Ambient and surface temperature above 8 °C.

For absorbent interior mineral substrates.

Stir well before use.

Apply evenly by brush, roller, or spray.

Apply 1 or 2 coats depending on substrate and colour.

Ensure adequate ventilation during application and drying.

Coats & recoating: 1 or 2 coats recommended. Recoating after sufficient drying. Drying time depends on temperature, humidity, ventilation, and substrate absorbency.

Tools: Brush, Roller, Spray.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in