



Lime Brush Rendering 667

Highly breathable, fine-grained textured plaster for interior walls.
Mold-preventing and moisture-regulating properties, particularly suitable for humid rooms.

For all interior absorbent mineral surfaces like lime plaster, rendering, lime sand brick, cement, aerated concrete, brick, loam rendering. Solvent free, permeable to water vapour, protects against infestation of germs and mould due to the high alkalinity. Matt finish, can be recoated many times. Mineral surfaces will be completely silicified.

Drying Time

Approx. 12 hours at 20°C/50% RH.
Subsequent coats after 24 hours.

Coverage

Coverage: approx. 30-55 sq ft per litre per coat.

Pack Size	Coverage
2,5l	8 m ²
10l	30 m ²

Tool Cleaning

Immediately after use, clean tools with water.

Storage

Store in a dry and cool place, protect from freezing. Shelf life in closed packaging is at least 1 year.

Disposal

Dispose of according to official regulations.

Technical Qualities

Highly breathable
Fine-grained texture (0.13mm)
Mold-preventing
Moisture-regulating
Lime-based

Composition

Water, slaked lime, chalk, marble powder, titanium dioxide, cellulose ether, organic binder
EU limit 30 g/l, cat a

Safety Recommendations

Causes skin irritation.
Causes serious eye damage.
May irritate respiratory tract.
Wear protective gloves, clothing, eye and face protection.



Lime Brush Rendering 667

Highly breathable, fine-grained textured plaster for interior walls.
Mold-preventing and moisture-regulating properties, particularly suitable for humid rooms.

Application Instructions

Stir thoroughly.

Apply evenly with brush or roller in all directions.

Two coats typically required, undiluted.

Tintable with lime-fast pigments (max 20%).

Tools: Brush, Roller.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in