



Interior Smoothing and Texturing Filler 684

Gypsum-based wall filler for interior use. Dries crack-free even in larger thicknesses, tintable with LEINOS pigment concentrates.

For interior use for finishing walls and ceilings. For filling cracks and holes as well as joints between plasterboard and other building boards. For securing wall plugs and inserting fixtures during installation work. For decorating walls and ceilings with texturing filler. White, matt. Ready mixed and can be coloured as required using LEINOS pigment concentrate 668. See technical data sheet 668.

Drying Time

Full curing required before sanding, painting, or wallpapering.

Coverage

Coverage varies by application thickness.

| Pack Size | Coverage |
|-----------|------------------------------------|
| 5kg | Depending on application thickness |

Tool Cleaning

Immediately after use, clean tools with water.

Storage

Store in a dry and cool place, protect from freezing. Shelf life in closed packaging is at least 2 years.

Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 12.

Technical Qualities

Gypsum-based filler
 Crack-free drying
 Tintable with pigments
 For seams and screw holes
 Powder form

Composition

Finely ground calcium sulfate (natural gypsum), calcium carbonate, methylcellulose

Safety Recommendations

Keep from children.
 Prevent environmental release.



Interior Smoothing and Texturing Filler 684

Gypsum-based wall filler for interior use. Dries crack-free even in larger thicknesses, tintable with LEINOS pigment concentrates.

Application Instructions

Mix 1 kg filler with 600 ml water.

Press into holes/cracks, then level.

Full curing required before sanding or painting.

Minimum +5°C.

Tools: Putty knife, Sponge board, Mixing container.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in