



Resin Lacquer Primer 810

Fast-drying, easily sanded primer for wood, stone, and metal surfaces. Suitable for interior and exterior use with good filling and opacity.

Drying Time

Dust-dry approx. 3 hours. Sandable and recoatable after 24 hours.

Coverage

Coverage: approx. 135-180 sq ft per litre per coat.

Tool Cleaning

LEINOS Verdünnung 200

Storage

Store in a dry and cool place, protect from freezing. Shelf life in closed packaging is at least 2 years.

Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 11.

Technical Qualities

Fast-drying primer
Easily sandable
Good filling and opacity
Water vapor permeable
Biocide-free

Composition

Plant oil-based binder, isoparaffins, titanium dioxide, chalk, talc, drying agents
EU limit cat g

Safety Recommendations

Keep away from children.
Oil-soaked materials pose self-ignition risk.
Respiratory protection required when spraying.



Resin Lacquer Primer 810

Fast-drying, easily sanded primer for wood, stone, and metal surfaces. Suitable for interior and exterior use with good filling and opacity.

Application Instructions

Stir thoroughly.

Apply by brush, roller, or spray.

Temperature above 15°C.

Protect from rain, wind, sun during drying.

Tools: Brush, Roller, Spray.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in