



Finishing Lacquer 840

High-coverage, silk-gloss, weather-resistant cover lacquer for interior and exterior wood. Available in 10 colours, all mutually mixable.

Top coating for the decorative finish or renovation coating of wood, metal or stoneware surfaces indoors and outdoors. Suitable for dimensionally stable wooden components such as windows and doors, limited dimensionally stable wooden components such as garden sheds, roof soffits, exterior gates and non-dimensionally stable wooden components such as fences, carports and palisades. Topcoat can be used for radiators. Not suitable for coating floor surfaces, anodized aluminium and galvanized surfaces. High weather and light resistance, low yellowing, high opacity/good edge coverage, biocide-free. The product is easy to apply and produces a silky gloss surface.

Color

White, Black, Anthracite Grey, Light Grey, Fir Green, Dove Blue, Nordic Red, Yellow, Blue, Leaf Green.

Drying Time

Dust-dry approx. 8 hours. Grip-firm approx. 12 hours.
Sandable/overcoatable after 24 hours.

Coverage

Coverage: approx. 110-155 sq ft per litre per coat.

Pack Size	Coverage
0,25l	3 m ²
0,75l	9 m ²
2,5l	29,5 m ²

Tool Cleaning

LEINOS Verdünnung 200

Storage

Store in a dry and cool place, protect from freezing. Shelf life in closed packaging is at least 2 years.

Disposal

Dispose of according to official regulations. Disposal code: EAK/EWC 08 01 11.

Technical Qualities

Silk-gloss finish
Weather-resistant
High opacity
Available in 10 colours
Biocide and aromatic-free

Composition

Plant oil-based binder, aliphatic hydrocarbons, titanium dioxide, inorganic/organic pigments, mineral fillers, additives, drying agents
EU limit 400 g/l, cat e

Safety Recommendations

Harmful to aquatic organisms.
Contains cobalt octoate (allergen).
Oil-soaked materials — self-ignition risk.



Finishing Lacquer 840

High-coverage, silk-gloss, weather-resistant cover lacquer for interior and exterior wood. Available in 10 colours, all mutually mixable.

Application Instructions

Stir thoroughly.

Apply by brush, roller, or spray.

Sand lightly (P180) between coats.

Protect from rain and sun during drying.

Tools: Brush, Roller, Spray.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in