



Weatherproof Paint Oil-Based 850

Oil-based, silk-gloss weatherproof paint for exterior timber: cladding, fences, sheds and rough-sawn boards. An elastic, vapour-permeable film with protection against fungal attack, in nine colours.

Open-pored, silk-gloss cover coat for all exterior timber structures; well suited to rough-sawn timber. Produces an elastic paint film that is weather- and UV-resistant and permeable to water vapour, with film protection against fungal attack. Saliva- and sweat-resistant to DIN 53160. Untreated, rough-sawn timber is brushed down and primed with LEINOS Impregnation Wood Primer 150, then painted in two sparing coats above 15 °C. Not for window rebates, seating surfaces, floors or other horizontal surfaces exposed to the weather.

Color

014 Corn Yellow, 057 Swedish Red, 064 Earth Brown, 104 Vine Black, 123 Frisian Blue, 204 Antique White, 400 Fir Green, 401 Steel Grey, 733 Anthracite Grey.

Drying Time

At 20 °C and 50 % relative humidity: dust-dry after approx. 12 hours; dry and recoatable after approx. 24 hours.

Coverage

Approx. 55–85 ml per m² per coat on planed or sanded wood — about 127–196 sq ft per litre per coat. Rough-sawn wood takes a little more.

Pack Size	Coverage
0.75 l	approx. 9–14 m ² per coat (55–85 ml/m ²)
2.5 l	approx. 29–45 m ² per coat (55–85 ml/m ²)

Tool Cleaning

LEINOS Thinner 200

Storage

Store cool and dry. Unopened, it keeps for at least 2 years. Close opened tins tightly and decant leftovers into a smaller container; if a skin has formed in the tin, lift it off carefully and do not stir it in.

Technical Qualities

Silk-gloss, opaque colour for exterior timber
Elastic, weather- and UV-resistant film
Open-pored and vapour-permeable
Film protection against fungal attack
Nine colours, all mixable with one another
Suits rough-sawn timber

Composition

Linseed oil, Wood oil, Castor oil, Natural resin esters, Isoparaffins, Kaolin, Chalk, Silica, Alumina, Micro-wax, Mineral pigments, Zinc oxide, Iodopropynyl butyl carbamate, Drying agents.

The maximum content of Volatile Organic Compounds (VOC) in this product is 290 g/l. It complies with the European VOC standard, which allows a maximum of 300 g/l (Category "d").

Safety Recommendations

Contains iodopropynyl butyl carbamate (below 0.6 %). May cause allergic reactions.

Repeated contact may cause dry or cracked skin.

Harmful to aquatic life with long-lasting effects. Avoid release to the environment.

Rags and materials soaked with wet oil can self-ignite. Keep them airtight in a metal container or under water, then dispose of them.

Wear approved respiratory protection when spraying and a fine-dust mask when sanding.

Keep out of reach of children.

Technical Standards

DIN 53160

Disposal

EAK/EWC waste code 08 01 11 ·
GISCODE BSL10. Take contents and
container to a suitable recycling or
disposal facility.



Weatherproof Paint Oil-Based 850

Oil-based, silk-gloss weatherproof paint for exterior timber: cladding, fences, sheds and rough-sawn boards. An elastic, vapour-permeable film with protection against fungal attack, in nine colours.

Application Instructions

Suitable substrates: Exterior timber structures, Rough-sawn timber, Timber cladding and board facades, Fences, sheds, gates and carports.

Not suitable for: Window rebates, Seating surfaces, Floors and other horizontal surfaces exposed to the weather.

Conditions: Air and surface temperature above 15 °C. The paint dries by taking up oxygen from the air: keep the air moving.

The surface must be dry, sound, clean and free of grease and dust.

Brush down untreated, rough-sawn timber and prime it with LEINOS Impregnation Wood Primer 150.

Scrape out resin pockets and clean them with LEINOS Thinner 200.

Stir thoroughly. The paint is ready to use.

Apply sparingly by brush, roller or airless spray above 15 °C. Two coats are required.

Recoat after about 24 hours at 20 °C.

Coats & recoating: Two coats are required. Recoat after approx. 24 hours at 20 °C.

Tools: Brush, Roller, Airless spray (nozzle 0.23–0.33 mm, approx. 30°, filter approx. 180 mesh), Stiff brush for rough-sawn timber.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in