



Weatherproof Paint Water-Based 855

Solvent-free, matt, water-based paint for untreated exterior timber, rough-sawn boards included. Breathable, easy to renovate, with film protection against fungal attack. Corn Yellow or Swedish Red.

Solvent-free, matt, water-based coating for all untreated exterior timber structures; well suited to rough-sawn timber. Good hiding power, permeable to water vapour, easy to renovate, with film protection against fungal attack. Brush out untreated, rough-sawn wood beforehand and apply by brush above 10 °C. Not suitable for oak.

Color

014 Corn Yellow, 057 Swedish Red.

Drying Time

At 20 °C and 50 % relative humidity: dust-dry after approx. 2 hours; dry and recoatable after approx. 24 hours.

Coverage

Approx. 55–85 ml per m² per coat on planed or sanded wood — about 127–196 sq ft per litre per coat. Rough-sawn wood takes a little more.

Pack Size	Coverage
2.5 l	approx. 29–45 m ² per coat (55–85 ml/m ²)
10 l	approx. 118–182 m ² per coat (55–85 ml/m ²)

Tool Cleaning

Thin with up to 20 % water. Clean with water and LEINOS Intensive Cleaner 935; LEINOS Thinner 200 for stubborn residue.

Storage

Store cool and dry. Unopened, it keeps for at least 2 years. Close opened containers tightly and decant leftovers into a smaller container.

Disposal

EAK/EWC waste code 08 01 20 · GISCODE BSW50. Take contents and container to a suitable recycling or disposal facility.

Technical Qualities

Solvent-free, water-based: VOC 1 g/l

Matt, opaque colour

Vapour-permeable

Easy to renovate

Film protection against fungal attack

Suits rough-sawn timber

Composition

Water, Linseed oil, Rye flour, Bentonite, Ferrous sulphate, Iron oxide pigments, Potassium oleate, Iodopropynyl butyl carbamate, Drying agents.

The maximum content of Volatile Organic Compounds (VOC) in this product is 1 g/l. It complies with the European VOC standard, which allows a maximum of 30 g/l (Category "a").

Safety Recommendations

Not classified as hazardous.

Contains 1,2-benzisothiazol-3(2H)-one. May cause allergic reactions.

Avoid release to the environment.

Keep out of reach of children.



Weatherproof Paint Water-Based 855

Solvent-free, matt, water-based paint for untreated exterior timber, rough-sawn boards included. Breathable, easy to renovate, with film protection against fungal attack. Corn Yellow or Swedish Red.

Application Instructions

Suitable substrates: Untreated exterior timber structures, Rough-sawn timber, Board fences and outbuildings.

Not suitable for: Oak, Previously painted or varnished wood.

Conditions: Air and surface temperature above 10 °C.

The wood must be dry, sound, clean and free of grease, resin and dust.

Brush out untreated, rough-sawn wood beforehand.

Stir carefully. The paint is ready to use; it can be thinned with up to 20 % water.

Apply by brush at air and surface temperatures above 10 °C.

Recoat after about 24 hours at 20 °C.

Coats & recoating: Recoat after approx. 24 hours at 20 °C, until the colour covers evenly.

Tools: Brush, Stiff brush for rough-sawn timber.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in