



Anti-Greying Fluid 940

Water-based cleaner for greyed garden furniture and decking, hardwood or softwood. Oxalic acid and coconut-oil surfactants lift the grey; the wood is then re-oiled with Teak Oil 223 or Terrace Wood Oil 236.

Cleaner for greyed garden furniture of hardwood and softwood; also for greyed decking and terrace wood. Cleans reliably and removes the greying by brightening the wood, with active ingredients from coconut fatty acid and oxalic acid. Do not apply in direct sunlight. Apply undiluted and thinly with a brush or cloth, leave to work for 15 minutes (up to 1 hour on heavy greying) while keeping the wood moist, scrub with a root brush and plenty of water, rinse thoroughly to neutralise, and allow 1–2 days to dry. Then sand lightly and treat with LEINOS Teak Oil 223 or Terrace Wood Oil 236.

Drying Time

The wood dries for 1–2 days after the final rinse, before the light sand and the oil.

Coverage

Approx. 100–125 ml per m² on smooth surfaces — about 86–108 sq ft per litre. Rough-sawn or profiled wood takes more.

Pack Size	Coverage
0.5 l	approx. 4–5 m ² (100–125 ml/m ²)
2.5 l	approx. 20–25 m ² (100–125 ml/m ²)

Tool Cleaning

Use undiluted. Rinse tools with water after use.

Storage

Store dry, cool and frost-free. Unopened, it keeps for at least 2 years.

Disposal

EAK/EWC waste code 07 06 01. Do not let the product into drains or waterways. Dispose of contents and container at a suitable recycling or disposal facility; fully emptied containers can be recycled.

Technical Qualities

Lifts the grey from weathered exterior wood

Hardwoods and softwoods

Water-based: oxalic acid and coconut-oil surfactants

15 minutes to 1 hour contact, then scrub and rinse

The step before Teak Oil 223 or Terrace Wood Oil 236

Composition

Water, Oxalic acid, Coconut oil surfactants, Methyl cellulose, Vegetable-based emulsifier.

VOC content: 0.1 g/l. A water-based cleaner, not a coating.

Safety Recommendations

Not classified as hazardous, but the fluid is acidic (pH 2.2). Wear safety goggles and nitrile gloves while applying and scrubbing.

If medical advice is needed, have the container or label at hand. Keep out of reach of children.

Avoid release to the environment. Slightly hazardous to water (WGK 1): do not pour the product into drains or waterways.

Do not work in direct sun — the fluid dries too quickly and stops working.



Anti-Greying Fluid 940

Water-based cleaner for greyed garden furniture and decking, hardwood or softwood. Oxalic acid and coconut-oil surfactants lift the grey; the wood is then re-oiled with Teak Oil 223 or Terrace Wood Oil 236.

Application Instructions

Suitable substrates: Greyed garden furniture of hardwood, Greyed garden furniture of softwood, Greyed decking and terrace boards.

Not suitable for: Wood under an intact varnish or paint film, Indoor surfaces and oiled floors — use Vegetable Soap 930, Application in direct sun.

Work in the shade, never in direct sun. On hot days, wet the wood lightly first.

Shake the container briefly.

Brush on undiluted and thin with a brush or cloth, approx. 100–125 ml per m².

Leave it to work for 15 minutes, up to 1 hour on heavy greying. Keep the wood moist.

Scrub thoroughly with a root brush and plenty of water.

Rinse thoroughly with water to neutralise, and leave the wood to dry for 1–2 days.

Sand lightly, then oil with LEINOS Teak Oil 223 or Terrace Wood Oil 236.

Coats & recoating: One application. On heavy greying, extend the contact time up to 1 hour rather than applying twice, and keep the wood moist throughout.

Tools: Brush or cloth, Root brush (stiff scrubbing brush), Hose or buckets of clean water, Fine abrasive for the light sand before oiling, Safety goggles and nitrile gloves.

This technical specification is for information and instruction purposes only. The guidelines are based on our latest expert data. There is no legal liability arising from the technical specification. If you have any doubts, please consult the seller or manufacturer.

Manufacturer

Reincke Naturfarben GmbH
Industriestraße 3
21640 Horneburg, Germany
Tel. +49 (0) 41 63 - 86 74 7-0
www.leinos.de

Distributor in India

Leinos Organic Paints Private Limited
GSTIN - 07AAFCL0615C1Z3
646/1, Zero Number Rd, Anand Gram,
Ghitorni, New Delhi 110030, India
+919997897474 | sales@leinos.in